

FS-1010

**Print
System**

Desktop Printing
System for the
Busy User

15 Pages Per Minute
with an Outstanding
600 DPI Quality

Diverse Array
of Connectivity
Options for
Connection to
any Environment

High Memory
Capacity to
Accommodate
the Most Resource
Intensive Requests

Low Total Cost of
Ownership (TCO)

One
company



Where Documents Are Going

FS-1010



Shown with optional
250 sheet tray.

Specifications

Technology Configuration: Imaging System: Resolution: Drum: Fusing: Size/Weight: Electrical Requirements: Maximum Duty Cycle:	Desktop Monochrome Printer Laser, Monocomponent Toner Fast 1200 dpi (1800 x 600), 600 x 600 dpi, 2400 x 600 dpi (KIR*) OPC Drum Heat/Pressure 14.9"W x 8.7"H x 14.7"D/21.0 lbs 120V, 60Hz 10,000 Pages
Output Speeds Warm Up: First Print Out Time: Pages Per Minute:	Less than 15 Seconds from Cold Start Less than 12 Seconds Up to 15 Letter
Paper Handling Standard Paper Supply: Min./Max. Paper Size: Paper Weight: Input Material: Paper Output: Optional Paper Sources:	One 250 Sheet Letter Cassette plus 50 Sheet Multi-Purpose Tray 2.8" x 5.8"/8.5" x 14" 16-28 lb via Paper Cassette, up to 43 lbs. via MPT Bond Paper, recycled paper, transparencies, labels, envelopes 150 Sheet Output Tray 250 Sheet Paper Feed Unit (up to Legal size)
Controller CPU/MHz: Interfaces: Network Operating System: Protocol: Print Memory: PDL/Emulations: Fonts:	PowerPC405/200MHz Standard IEEE 1284 Parallel, USB1.1, Optional IB-10E Serial Interface, IB-21E 10/100BaseTX Network Interface Windows™ 95/98/NT3.5x/NT4.x/2000, NetWare™ 3.x/4.x/5.x/NDS, AppleTalk, UNIX TCP/IP, IPX/SPX, AppleTalk, NetBEUI Standard 16MB, upgradeable to 144MB via 100 pin DIMMs PCL6/5e, KPDL2 (PS2), PRESCRIBE, IBM Proprinter x 24E, Epson LQ-850, Diablo 620, KC-GL 80 fonts (PCL, KPDL2)
Hardware Options Network Interface: Additional Options: In Carton Items:	IB-21e 10BaseT, 10Base2, 10\100BaseTX Network Interface Serial Interface, CF Card Mainframe, starter Toner, Digital Library CD ROM containing Drivers, Documentation, Utilities, KM NET VIEWER Network Administration Software

*Kyocera Image Refinement

Fast Results

A 200 MHz CPU, quick 12 second First Print, and up to 15 Letter Size Pages Per Minute ensures fast turnaround of lengthy documents.

At Home in Any Neighborhood

Whether you connect locally via Parallel, Serial, USB or Ethernet, the FS-1010 blends seamlessly and provides support for all popular PDLs.

Excellent Image Quality

The FS-1010 delivers outstanding image quality at 600 dpi, providing the user with a clear, sharp image every time.

Large Capacity Memory

With 16MB RAM standard and the ability to expand up to 144MB, the FS-1010 can handle even the most complex documents.

Low Total Cost of Ownership

With a high yield toner cartridge of 6K prints, the FS-1010 is ideal for the print-intensive user who is looking to lower the overall cost of printing. Plus, our ECOSYS® design ensures a low cost per print and reduced overall Total Cost of Ownership.

Specifications and design are subject to change without notice.
All trademarks and registered trademarks are the property
of their respective manufacturers.

Visit www.kyoceramita.com

Item code #87164012



Where Documents Are Going

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2001 Kyocera Mita America, Inc.